

TECHNICAL DATA SHEET

PRODUCT:"BULLDOG " RUBBER LUBRICANT



PRODUCT DESCRIPTION

"BULLDOG " Rubber Lubricant is a smooth free flowing lubricant ,ideal for fitting of SWR pipes having rubber ring gaskets.It is compatible with water.

APPLICATION AREAS

In piping for fitting of SWR pipes and also in automotive and industry for fitting, Hydraulic and braking pipes. Also for protecting and lubricating rubber bushes, seals,O- rings etc.

DIRECTIONS FOR USE

Apply a thin even coating on the rubber ring of the SWR pipe. Gently force the pipe into the socket. The rubber lubricant will ensure that pipe fits inside smoothly.

Apply a thin film to seals rubber parts for smooth fitting & protection.

CLEANUP

Clean up with Acetone and Toulene.

DISCLAIMER

The information contained herein is given in good faith , based on our tests & knowldege of the product; as a guide .

The responsibility is of the user to verify its usability for any application. The company ,The Standard Products Mfg. Co. Mumbai , disclaims all warranties expressed or implied and takes no responsibilities for any loss or damage arising from the use of its products.

For further information please contact:

The Standard Products Mfg. Co.

2/14, Marol Co-op. Indl. Estate, Makawana Road,
Marol, Andheri (E), Mumbai – 400 059.
Customer Support : 2850 0970 / 2859 0668
E-mail :spm59@gmail.com

Properties of Components (before mixing)

Appearance	Milkish colour paste
Specific gravity	0.68 g/ml
Odour	Mild ethereal
Solubility in water	Negligible

SAFETY INSTRUCTION

- 1.Keep away from children.
- 2.Avoid excessive contact with body. Clean with plenty of water in case of eye contact.
- 3.Cannot be ingested. Lethal if ingested.
- 4.Do not induce vomiting,in case of ingestion. Consult a physician immediately.
- 5.Do not inhale or used in closed spaces.